
EV Power EVH-12V56AH LiFePO4 Battery

Features of LiFePO4 Battery

- Longer Cycle Life: Offers up to 20 times longer cycle life and five times longer float/calendar life than lead acid battery, helping to minimize replacement cost and reduce total cost of ownership.
- **Lighter Weight:** About 40% of the weight of a comparable lead acid battery. A 'drop in' replacement for lead acid batteries.
- Higher Power: Delivers twice power of lead acid battery, even high discharge rate, while maintaining high energy capacity.
- Wider Temperature Range: -20 ℃~60 ℃.
- Superior Safety: Lithium Iron Phosphate chemistry eliminates the risk of explosion or combustion due to high impact, overcharging or short circuit situation.
- Increased Flexibility: Modular design enables deployment of up to four batteries in series and up to ten batteries in parallel.



Physical Dimension









Application

- Electric vehicles, electric mobility
- Solar/wind energy storage system
- UPS, backup power
- Telecommunication
- Medical equipment
- Lighting


Specification

	Nominal Voltage	12.8V
Electrical Characteristics	Nominal Capacity	56Ah
	Energy	716.8Wh
	Internal Resistance	≤4 0m Ω
	Cycle Life	>2000 cycles @1C 100%DOD
	Months Self Discharge	<3%
	Efficiency of Charge	100% @0.5C
	Efficiency of Discharge	96~99% @1C
Standard Charge	Charge Voltage	14.6±0.1V
	Charge Mode	0.2C to 14.6V, then 14.6V, charge current to 0.02C (CC/CV)
	Charger Current	25A
	Max. Charge Current	50A
	Charge Cut-off Voltage	14.6V±0.1V
Standard Discharge	Continuous Current	70A
	Max. Pulse Current	110A(<2s)
	Discharge Cut-off Voltage	10V
Environmental	Charge Temperature	0 $^{\circ}$ to 45 $^{\circ}$ (32F to 113F) @60 \pm 25% Relative Humidity
	Discharge Temperature	-20 $^{\circ}\mathrm{C}$ to 60 $^{\circ}\mathrm{C}$ (-4F to 140F) @60 \pm 25% Relative Humidity
	Storage Temperature	0 $^{\circ}$ C to 40 $^{\circ}$ C (32F to 104F) @60 \pm 25% Relative Humidity
	Water Dust Resistance	IP56
	Cell & Method	26650 3.6Ah 4S16P
	Plastic Case	ABS
	Dimensions (mm./in.)	229x138x215mm
Mechanical	Weight (kg./lbs.)	7.5Kg
	Terminal	M8

EV Power EVH-12V56AH LiFePO4 Battery


Different Rate Discharge Curve

Different Rate Discharge Curve @25℃




State of Charge Curve

State of Charge Curve @0.5C 25°C




Cycle Life Curve

Different DOD Discharge Cycle Life Curve @1C




Different Temperature Discharge Curve

Different Temperature Discharge Curve @0.5C



Charging Characteristics

Charging Characteristics @0.5C 25 ℃



Self Discharge Characteristics Curve

Different Temperature Self Discharge Curve

